# DATA SHEET DEVIO® DCM-1 BEAMTRACKING™ CEILING MICROPHONE



The DCM-1 is a ceiling microphone for use in Devio® systems. Comprising a pendant microphone and plenum box, each microphone includes Beamtracking™ technology with three 120-degree zones, providing full 360-degree coverage of the meeting space. The DCM-1 microphone actively tracks and intelligently mixes conversations from around the table, allowing far-end conference participants to experience the conversation naturally. The Devio DCM-1 has four software-selectable elevation angle modes for optimal sound pickup, and each plenum box comes with an additional RJ-45 connector for daisy-chain connections. A maximum of two DCM-1 microphones are permitted per daisy chain. The Devio DCM-1 is well suited for huddle rooms or small conference rooms that require cost effective, high-quality audio solutions.

### **FEATURES**

- Beamtracking technology actively tracks and intelligently mixes conversations
- Three 120-degree zones for 360 degrees of coverage
- Three LED mute status indicators
- Four selectable elevation angle modes
- User-adjustable mic height
- Easy single-cable installation process
- Optional tile bridge mounting accessory available

- Pendant microphone available in either white or black
- Evaluated to the requirements of UL 2043 and is suitable for use in air handling spaces
- Additional RJ-45 for daisy-chain connection to another DCM-1 microphone (maximum of two mics per daisy chain)
- CE marked, UL listed, and RoHS compliant
- Covered by Biamp Systems' two-year warranty

NOTE: DCM-1 CEILING MICROPHONES AND DTM-1 TABLETOP MICROPHONES CANNOT BE DAISY-CHAINED TOGETHER.



#### **ARCHITECTS & ENGINEERS SPECIFICATIONS**

The Beamtracking™ ceiling microphone shall be designed exclusively for use with Devio® systems. The Beamtracking ceiling microphone shall utilize a proprietary network via an RJ-45 connector for audio networking as well as software configuration and control. The Beamtracking ceiling microphone shall contain eight-element microphones, and shall provide three 120-degree zones for 360 degrees of coverage. The Beamtracking ceiling microphone shall offer multidirectional beamforming and automatic signal tracking capabilities. The Beamtracking technology shall operate in conjunction with acoustic echo cancellation technology (AEC) in accordance with U.S. Patent 9659576. The Beamtracking ceiling microphone shall offer simple installation and microphone height adjustment, and shall be mountable on a ceiling tile or in open-ceiling environments. The Beamtracking ceiling microphone shall be suitable for use in air handling spaces in accordance with UL 2043, and shall provide a second RJ-45 connector to allow an additional Beamtracking ceiling microphone to be daisy-chained together. The Beamtracking ceiling microphone shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be two years. The Beamtracking ceiling microphone shall be Devio DCM-1.

#### **DEVIO DCM-1 SPECIFICATIONS**

PENDANT MICROPHONE

Microphone Technology: 8-Element Digital Array

Frequency Response (150 Hz - 16 kHz): ± 3 dB

**Polar Pattern:** Active Beamformed

Sensitivity (94 dB SPL, 1 kHz): > 70 dB, A-Weighted

Maximum SPL (at 0.5% THD): 106 dB SPL

**Dynamic Range (THD+N < 10%):** 92 dB, A-Weighted

**Automatic Noise Suppression:** 4 modes: Off, Low (Default),

Medium, High

**Selectable Elevation Modes:** 4 modes: multiple

30° selections

30 36166110113

< 1 W, phantom powered from plenum box

Indicators: Mute Indicator

(Green/Red LED)

**Digital Interface:** Custom/Proprietary

**Connector:** Custom 2-pin (cable length

10 feet [3 meters])

**Overall Dimensions:** 

Power:

 Height:
 2 inches (51 mm)

 Width:
 2.5 inches (63 mm)

 Depth:
 2.5 inches (63 mm)

 Weight:
 0.38 lbs (0.17 kg)

**PLENUM BOX** 

**Power:** < 1 W, phantom powered

from SCR-20/SCR-25

Indicators: Connection Indicator (Green LED)

**Digital Interface:** Custom/Proprietary

**Connectors:** Two RJ-45: one between DCM-1

plenum box and SCR-20/SCR-25, the other between DCM-1

plenum box and additional

DCM-1 plenum box

**Max Distance Between Devices:** 49 feet (15 meters) from

SCR-20/SCR-25 to DCM-1;

49 feet (15 meters) for daisy-chained connections

between DCM-1 microphones

**Overall Dimensions:** 

 Height:
 2 inches (51 mm)

 Width:
 4 inches (102 mm)

 Depth:
 5.4 inches (137 mm)

 Weight:
 0.86 lbs (0.39 kg)

**Environmental:** 

**Ambient Operating** 

**Temperature Range:** 32-104° F (0-40° C)

**Humidity:** 0-95% relative humidity (non-condensing)


**Altitude:** 0-6,600 ft (0-2000 m) MSL

Compliance:

FCC Part 15B (USA)
CE marked (Europe)
UL and C-UL listed (USA and Canada)
ROHS Directive (Europe)
Evaluated to the requirements
of UL 2043 and is suitable for


use in air handling spaces

BEAMFORMING RANGE Polar pattern shown at 1kHz Zone 1



Biamp, Devio, and Beamtracking are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.







## Dieses Dokument, wird Ihnen zur Verfügung gestellt von:

ppm-stuttgart 🚅 💡 dem systemhaus für digitale technik direkt bei stuttgart













Viele weitere Infos finden Sie unter:

ppm-stuttgart.de oder DIKTAT-STUTTGART.de