

## Product Specification

### 1、Product Feature



### 2、Camera Parameters

Pixel	12M
Output Resolution	YUY2(30fps): 640 × 480、640 × 360、480 × 270、 352 × 288、320 × 240 MJPEG(30fps): 3840 × 2160( 24fps )、3840 × 1376、3840 × 962、 2560 × 1440、1920 × 1080、1280 × 720、 1024 × 576、960 × 544、640 × 480、640 × 360 H264(30fps): 1280 × 720、1024 × 576、960 × 544、 640 × 480、640 × 360

# MAXHUB

Output Format	MJPEG、H.264、YUY2
Focus Method	Fixed
Focus Distance	1.5m
Maximum field of view FOV	180°
Aperture	2.2
Minimum Illumination	10lux

## 3、Microphone Parameters

Quantity	2
Pickup Distance	0~4m

## 4、I/O Port

USB Type-A(Host)	1
USB Type-C(Device)	1

## 5、Physical Specifications

Dimension L × H × D		146 × 32.1 × 74.2mm
Dimension (package) L × W × H	1PCS	175 × 175 × 44mm
	30PCS	543 × 244 × 390mm
Net Weight		220g
Gross Weight	1PCS	551g
	30PCS	TBD

# MAXHUB

---

## 6、Accessories

USB Cable	× 1
Wall Mount	× 1

## 7、Environmental Conditions

Operation Temperature	0°C~40°C
Operation Humidity	10%~90%RH
Storage Temperature	-20°C~60°C
Storage Humidity	10%~90%
Altitude	Below 5000 meters

## 8、Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product.

The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product.

The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance.

Should the above-mentioned change in the document become necessary, the document may be updated without written notice.